

BS IEC 60317-4:2015



BSI Standards Publication

Specifications for particular types of winding wires

Part 4: Solderable polyurethane enamelled round copper wire, class 130

National foreword

This British Standard is the UK implementation of IEC 60317-4:2015. It supersedes BS EN 60317-4:1995 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee L/-/99, Miscellaneous Standards - Electrical.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.
Published by BSI Standards Limited 2015

ISBN 978 0 580 83424 0
ICS 29.060.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2015.

Amendments/corrigenda issued since publication

| Date | Text affected |
|------|---------------|
|------|---------------|



INTERNATIONAL STANDARD

NORME INTERNATIONALE

Specifications for particular types of winding wires –
Part 4: Solderable polyurethane enamelled round copper wire, class 130

Spécifications pour types particuliers de fils de bobinage –
Partie 4: Fil brasable de section circulaire en cuivre émaillé avec polyuréthane,
classe 130

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.060.10

ISBN 978-2-8322-2729-9

| |
|---|
| <p>Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.</p> |
|---|

CONTENTS

| | |
|--|----|
| FOREWORD..... | 3 |
| INTRODUCTION..... | 5 |
| 1 Scope..... | 6 |
| 2 Normative references..... | 6 |
| 3 Terms, definitions, general notes and appearance..... | 6 |
| 3.1 Terms and definitions..... | 6 |
| 3.2 General notes | 6 |
| 3.2.1 Methods of test | 6 |
| 3.2.2 Winding wire | 6 |
| 3.2.3 Appearance | 7 |
| 4 Dimensions | 7 |
| 5 Electrical resistance | 7 |
| 6 Elongation | 7 |
| 7 Springiness | 7 |
| 8 Flexibility and adherence | 7 |
| 9 Heat shock | 7 |
| 10 Cut-through | 7 |
| 11 Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,000 mm) | 7 |
| 12 Resistance to solvents..... | 8 |
| 13 Breakdown voltage | 8 |
| 14 Continuity of insulation | 8 |
| 15 Temperature index..... | 8 |
| 16 Resistance to refrigerants | 8 |
| 17 Solderability | 8 |
| 17.1 Nominal conductor diameters up to and including 0,100 mm..... | 8 |
| 17.2 Nominal conductor diameter over 0,100 mm | 9 |
| 18 Heat or solvent bonding | 9 |
| 19 Dielectric dissipation factor | 9 |
| 20 Resistance to transformer oil | 9 |
| 21 Loss of mass | 9 |
| 23 Pin hole test | 9 |
| 30 Packaging | 9 |
| Bibliography | 10 |
| Table 1 – Resistance to abrasion | 8 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 4: Solderable polyurethane enamelled round copper wire, class 130

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60317-4 has been prepared by IEC technical committee 55: Winding wires.

This fourth edition cancels and replaces the third edition published in 1990, Amendment 1:1997 and Amendment 2:1999. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- new 3.2.2 containing general notes on winding wire, formerly a part of the scope;
- new 3.2.3 containing requirements for appearance;
- revision to references to IEC 60317-0-1:2013 to clarify that their application is normative;
- consolidation of 17.1 and 17.2 of the solderability requirements;
- revision to Clause 19, dielectric dissipation factor;
- new Clause 23, pin hole test.

The text of this standard is based on the following documents:

| CDV | Report on voting |
|-------------|------------------|
| 55/1459/CDV | 55/1498/RVC |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be read in conjunction with IEC 60317-0-1:2013.

The numbering of clauses in this standard is not continuous from Clauses 20 and 30 in order to reserve space for possible future wire requirements prior to those for wire packaging.

A list of all parts in the IEC 60317 series, published under the general title Specifications for particular types of winding wires, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 60317 is one of a series which deals with insulated wires used for windings in electrical equipment. The series has three groups describing:

- 1) Winding wires – Test methods (IEC 60851 series);
- 2) Specifications for particular types of winding wires (IEC 60317 series);
- 3) Packaging of winding wires (IEC 60264 series).

SPECIFICATIONS FOR PARTICULAR TYPES OF WINDING WIRES –

Part 4: Solderable polyurethane enamelled round copper wire, class 130

1 Scope

This part of IEC 60317 specifies the requirements of solderable enamelled round copper winding wire of class 130 with a sole coating based on polyurethane resin, which may be modified provided it retains the chemical identity of the original resin and meets all specified wire requirements.

NOTE A modified resin is a resin that has undergone a chemical change, or contains one or more additives to enhance certain performance or application characteristics.

The range of nominal conductor diameters covered by this standard is:

- Grade 1: 0,018 mm up to and including 2,000 mm;
- Grade 2: 0,020 mm up to and including 2,000 mm.

The nominal conductor diameters are specified in Clause 4 of IEC 60317-0-1:2013.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60317-0-1:2013, Specifications for particular types of winding wires – Part 0-1: General requirements – Enamelled round copper wire

3 Terms, definitions, general notes and appearance

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in 3.1 of IEC 60317-0-1:2013 apply.

3.2 General notes

3.2.1 Methods of test

Subclause 3.2 of IEC 60317-0-1:2013 applies. In case of inconsistencies between IEC 60317-0-1 and this standard, IEC 60317-4 shall prevail.

3.2.2 Winding wire

Class 130 is a thermal class that requires a minimum temperature index of 130 and a heat shock temperature of at least 155 °C.

The temperature in degrees Celsius corresponding to the temperature index is not necessarily that at which it is recommended that the wire be operated and this will depend on many factors, including the type of equipment involved.

3.2.3 Appearance

Subclause 3.3 of IEC 60317-0-1:2013 applies.

4 Dimensions

Clause 4 of IEC 60317-0-1:2013 applies.

5 Electrical resistance

Clause 5 of IEC 60317-0-1:2013 applies.

6 Elongation

Clause 6 of IEC 60317-0-1:2013 applies.

7 Springiness

Clause 7 of IEC 60317-0-1:2013 applies.

8 Flexibility and adherence

Clause 8 of IEC 60317-0-1:2013 applies. The constant K used for the calculation of the number of revolutions for the peel test shall be 150 mm.

9 Heat shock

Clause 9 of IEC 60317-0-1:2013 applies. The minimum heat shock temperature shall be 155 °C.

10 Cut-through

No failure shall occur within 2 min at 170 °C.

11 Resistance to abrasion (nominal conductor diameters from 0,250 mm up to and including 2,000 mm)

The wire shall meet the requirements given in Table 1.

For intermediate nominal conductor diameters, the value of the next larger nominal conductor diameter shall apply.

Table 1 – Resistance to abrasion

| Nominal conductor diameter mm | Minimum average force to failure | Grade 1 | | Grade 2 | |
|----------------------------------|----------------------------------|--|----------------------------------|--|--|
| | | Minimum force to failure of each measurement | Minimum average force to failure | Minimum force to failure of each measurement | |
| | Minimum average force to failure | Minimum force to failure of each measurement | Minimum average force to failure | Minimum force to failure of each measurement | |

N

| | N | N | N | |
|-------|------|------|------|------|
| 0,250 | 2,30 | 1,95 | 4,10 | 3,50 |
| 0,280 | 2,50 | 2,10 | 4,40 | 3,70 |
| 0,315 | 2,70 | 2,30 | 4,75 | 4,00 |
| 0,355 | 2,90 | 2,50 | 5,10 | 4,30 |
| 0,400 | 3,15 | 2,70 | 5,45 | 4,60 |
| 0,450 | 3,40 | 2,90 | 5,80 | 4,90 |
| 0,500 | 3,65 | 3,10 | 6,20 | 5,25 |
| 0,560 | 3,90 | 3,30 | 6,65 | 5,60 |
| 0,630 | 4,20 | 3,55 | 7,10 | 6,00 |
| 0,710 | 4,50 | 3,80 | 7,60 | 6,45 |
| 0,800 | 4,80 | 4,10 | 8,10 | 6,90 |
| 0,900 | 5,20 | 4,40 | 8,70 | 7,40 |
| 1,000 | 5,60 | 4,75 | 9,30 | 7,90 |
| 1,120 | 6,00 | 5,15 | 10,0 | 8,50 |
| 1,250 | 6,50 | 5,55 | 10,7 | 9,10 |
| 1,400 | 7,00 | 5,95 | 11,4 | 9,70 |
| 1,600 | 7,50 | 6,35 | 12,2 | 10,4 |
| 1,800 | 8,00 | 6,80 | 13,1 | 11,1 |
| 2,000 | 8,60 | 7,30 | 14,0 | 11,9 |

12 Resistance to solvents

Clause 12 of IEC 60317-0-1:2013 applies.

13 Breakdown voltage

Clause 13 of IEC 60317-0-1:2013 applies. The elevated temperature shall be 130 °C.

14 Continuity of insulation

Clause 14 of IEC 60317-0-1:2013 applies.

15 Temperature index

Clause 15 of IEC 60317-0-1:2013 applies. The minimum temperature index shall be 130.

16 Resistance to refrigerants

Test inappropriate.

17 Solderability

17.1 Nominal conductor diameters up to and including 0,100 mm

The temperature of the solder bath shall be $(375 \pm 5) ^\circ\text{C}$. The maximum immersion time shall be 2 s.

The surface of the tinned wire shall be smooth and free from holes and enamel residues.

17.2 Nominal conductor diameter over 0,100 mm

The temperature of the solder bath shall be $(375 \pm 5) ^\circ\text{C}$. The maximum immersion time (in seconds) shall be the following multiple of the nominal conductor diameter (in millimetres) with a minimum of 2 s.

| Grade 1 | Grade 2 |
|---------|---------|
| 8 s/mm | 12 s/mm |

The surface of the tinned wire shall be smooth and free from holes and enamel residues.

18 Heat or solvent bonding

Test inappropriate.

19 Dielectric dissipation factor

Test to be agreed between purchaser and supplier.

The dielectric loss tangent at approximately 1 MHz shall not exceed 300×10^{-4} if the wire is to be used in high-frequency coils. Compliance shall be checked by a method agreed between purchaser and supplier.

20 Resistance to transformer oil

Test inappropriate.

21 Loss of mass

Test inappropriate.

23 Pin hole test

Clause 23 of IEC 60317-0-1:2013 applies.

30 Packaging

Clause 30 of IEC 60317-0-1:2013 applies.

Bibliography

IEC 60264 (all parts), Packaging of winding wires

IEC 60317 (all parts), Specifications for particular types of winding wires

IEC 60851 (all parts), Winding wires – Test methods

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With British Standards Online (BSOL) you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a BSI Subscribing Member.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a Multi-User Network Licence (MUNL) you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person

or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs

and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK



...making excellence a habit.™